

HARVIA M SERIES

WKPM3

The Harvia M3 has a classic design and is suitable for smaller, woodburning saunas. It turns a sauna bath into a pleasurable experience and adds a touch of traditional sauna atmosphere. The even heat and efficient air circulation guarantee an enjoyable bath.



Features

Main material : Steel

H x W x D : 710.0 x 390.0 x 450.0 mm

Net weight (kg) : 44.2


Installation location : Floor

ID	GTIN	Output (kW)	Sauna room size min - max m3
WKPM3	6417659024860	16.5 kW	6.0-13.0


Related products




WP220ST




WZ011115



WZ020115



WZ020130



WZ050M



Spare parts

Product	ID	Pcs
Furnace grate	ZKIP-10	1
Connection pipe	ZKIP-130	1
Ashpan RST Pro	ZKIP-720	1
Hinge pin	ZKIP-50	1
Air-flow spoiler M1/M3	ZKIP-630	1
Front plate M3 chrome	ZKIP-620	
Handle for stove + screws	ZKIP-670	1
Handle for ash box	ZKIP-680	
Stove door with glass	ZROST-048	
	ZKIP-570	
Handle and screws, Chrome	SPZKIP-670	
Adjustable legs for LG150/SL	SPZKIP-918	
Hinge pin	SPZKIP-50	
Door for stove with knob, black	SP010	
Air-flow spoiler M1/M3	SPZKIP-630	
Ashtray black, sauna heaters	SP682	
Cap for smoke hole (Ø 50 mm)	SPZKIP-170	
Glass 184x210x4 mm Stoves 2006-, transparent	SPZTS-36	
Stove door with glass (from 2006)	SP048	
Cast-iron grating 135x290mm, sauna heaters	SPZKIP-10	

Technical details

Technical data	Type / attribute	WKPM3
	Color	Black
	Power output	16.5 kW
	Stone sizes	Ø10–15 cm
	Stone amount (kg)	30
Dimensions	Product width	390
	Product height	710
	Product depth (mm)	450
	Net weight (kg)	44.2
	Gross weight	44.6
	Package width	500
	Package height	765
	Package depth	415
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	300
	Safety distance front (combustible materials)	300
	Safety distance right side (combustible materials)	300
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	300
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100



Technical details

Technical data	Type / attribute	WKPM3
	Safety distance behind (combustible materials)	300
	Safety distance (Ceiling)	1200
	Room min. height(depends on connections and therefore from output, star/delta)	1900
	Installation opening height	2000
	Installation opening width	890
	Installation opening depth	1030